

housings Duplex Plus 3P AX

for quick-fit cartridges with double O-ring



Medium Junior Master Senior

APPLICATIONS

Filtration and treatment of water with neutral pH and drinking water. The exclusive DUPLEX housings allow faster and safer installations of serial filtration units.

Domestic use: filtration and treatment of drinking water, protection of taps, boilers, washing machines, and other installations.

Technical use: pre-filtration, micro-filtration; protection of pumps, heating systems, softeners, demineralising and chlorine-removing appliances, reverse osmosis units.

WORKING CONDITIONS

Max working pressure _____ 8 BAR

Max working temperature _____ 45°C

SPECIFICATIONS

Non-toxic materials, suitable for drinking water.

Head and ring nut: reinforced polypropylene.


Transparent bowl: SAN.

O-ring: ETP.

Breather-valve: body polypropylene, O-ring ETP.

IN/OUT threads: CW 614 N brass inserts.

Cartridge height	housings with transparent bowl AS IN/OUT female threads with FO brass inserts	IN/OUT threads	mm	
			A	B
5"	Medium Duplex Plus 3P AFO AX AS	3/4"	191	275
5"	Medium Duplex Plus 3P BFO AX AS	1"	191	275
7"	Junior Duplex Plus 3P AFO AX AS	3/4"	241	275
7"	Junior Duplex Plus 3P BFO AX AS	1"	241	275
10"	Senior Duplex Plus 3P AFO AX AS	3/4"	315	275
10"	Senior Duplex Plus 3P BFO AX AS	1"	315	275
20"	Master Duplex Plus 3P AFO AX AS	3/4"	571	275
20"	Master Duplex Plus 3P BFO AX AS	1"	571	275



VARIANTS available on minimum quantity

FP female plastic IN/OUT threads, BSP type 3/4".

AB housings with opaque bowl, impermeable to the light.



TÜRK SU ARAŞTIRMA MERKEZİ

e-mail : bilgi@tusam.com.tr

web : www.tusam.com.tr

Phone : +90 850 302 0 392



wall bracket screws



3/4" and 1", brass nipples with O-ring