

LOFTOP Filter Cartridges

with absolute micron ratings ($\beta > 5000$)
depth filter cartridges

Specifications

Material:	100% pure polypropylene free of bonding agents polypropylene core
Diameter outside:	2,50" = 64 mm
Diameter inside:	1,06" = 27 mm
Length (inch):	9"3/4 - 10 - 20 - 30 - 40
(mm):	254 - 508 - 762 - 1016
Temperature:	80°C (for sterilisation 121°C)
Micron ratings:	0,5 - 1 - 3 - 5 - 10 - 20 - 30 - 50 - 70 - 90 - 120 μ
Flow rates (water):	0,9 - 1,0 - 1,1 - 1,4 - 1,6 - 2,0 - 2,6 - 3,0 - 3,0 - 3,0 - 3,0 m ³ /h
Differential pressure:	- 0,1 bar -



End configurations:	DOE (standard)
	DOE with foamed gaskets (G)
	SOE 226-O rings bayonet / spear (3)
	SOE 222-O rings / flat (4)

Some typical applications: water for dialysis, food, beverages, edible oils, pharmaceutical, electro plating, semiconductor manufacturing, chemicals,

petrochemicals, paints, inks and generally as pre-filter in order to save sub-micron absolute filters

Ordering information: LT - 10 - 5 - A - X

LOFTOP no. length micron rating absolute configuration