

housings 2P SX

for cartridges with standard flat seals



Cadet

Junior

Senior

APPLICATIONS

Filtration and treatment of water with neutral pH and drinking water.

Domestic use: filtration of drinking water, protection of taps, boilers, washing machines, and other installations.

Technical use: pre-filtration, micro-filtration; protection of pumps, heating systems, softeners, demineralising and chlorine-removing appliances, reverse osmosis units.

WORKING CONDITIONS

Max working pressure _____ 7 BAR

Max working temperature _____ 45°C

SPECIFICATIONS

Non-toxic materials, suitable for drinking water.

Head: ABS


Transparent bowl: SAN.

O-ring: ETP

Breather-valve: body polypropylene, O-ring ETP.

IN/OUT threads: CW 614 N brass inserts.

| Cartridge height | housings with transparent bowl AS IN/OUT female threads with FO brass inserts | IN/OUT threads | mm | |
|------------------|--|----------------|-----|-----|
| | | | A | B |
| 4" | Cadet 2P AFO SX AS | 3/4" | 169 | 133 |
| 4" | Cadet 2P BFO SX AS | 1" | 175 | 145 |
| 7" | Junior 2P AFO SX AS | 3/4" | 241 | 133 |
| 7" | Junior 2P BFO SX AS | 1" | 247 | 145 |
| 10" | Senior 2P AFO SX AS | 3/4" | 315 | 133 |
| 10" | Senior 2P BFO SX AS | 1" | 321 | 145 |



VARIANTS available on minimum quantity

FP female plastic IN/OUT threads, BSP type 3/4" e 1".

AB housings with opaque bowl, impermeable to the light.



TÜRK SU ARAŞTIRMA MERKEZİ
TÜSAM

e-mail : bilgi@tusam.com.tr

web : www.tusam.com.tr

Phone : +90 850 302 0 392



wall bracket screws



3/4" and 1"brass nipples with O-ring



4", 7", 10" diffuser tubes