housings Duplex Plus 3P SX

for cartridges with standard flat seals







APPLICATIONS

Filtration and treatment of water with neutral pH and drinking water. The exclusive Duplex housings allow faster and safer installation of serial filtration units.

Domestic use: filtration of drinking water, protection of taps, boilers, washing machines, and other installations.

Technical use: pre-filtration, micro-filtration; protection of pumps, heating systems, softeners, demineralising and chlorine-removing appliances, reverse osmosis units.

WORKING CONDITIONS

Max working pressure _	8 BAR
Max working temperatur	re 45°C

SPECIFICATIONS


Non-toxic materials, suitable for drinking water. Head and ring nut: reinforced polypropylene.


Transparent bowl: SAN.

O-ring: ETP

Breather-valve: body polypropylene, O-ring ETP. IN/OUT threads: CW 614 N brass inserts.

Cartridge	housings with transparent bowl AS	IN/OUT	mm	
height	IN/OUT female threads with FO brass inserts	threads	Α	В
5″	Medium Duplex Plus 3P AFO SX AS	3/4"	191	275
7″	Junior Duplex Plus 3P AFO SX AS	3/4"	241	275
10"	Senior Duplex Plus 3P AFO SX AS	3/4"	315	275
20"	Master Duplex Plus 3P AFO SX AS	3/4"	571	275





FP female plastic IN/OUT threads, BSP type 3/4".

AB housings with opaque bowl, impermeable to the



e-mail: bilgi@tusam.com.tr : www.tusam.com.tr web Phone: +90 850 302 0 392



screws



with O-ring





