# housings Plus 3P SX

# for cartridges with standard flat seals



# Ayrıntılı Bilgi ve Sipariş için :

e-mail : bilgi@tusam.com.tr web : www.tusam.com.tr Phone : +90 850 302 0 392



### **APPLICATIONS**

Filtration and treatment of water with neutral pH and drinking water.

Domestic use: filtration and treatment of drinking water, protection of taps, boilers, washing machines, and other installations.

Technical use: pre-filtration, micro-filtration; protection of pumps, heating systems, softeners, demineralising and chlorine-removing appliances, reverse osmosis units.

# **WORKING CONDITIONS**

Max working pressure	8 BAR
Max working temperature	45°C

### **SPECIFICATIONS**

Non-toxic materials, suitable for drinking water. **Head and ring nut:** reinforced polypropylene.

Transparent bowl: SAN.

O-ring: ETP

**Breather-valve:** body polypropylene, O-ring ETP. **IN/OUT threads:** CW 614 N brass inserts.

Cartridge	housings with transparent bowl AS	IN/OUT	mm	
height	IN/OUT female threads with FO brass inserts	threads	Α	В
5″	Medium Plus 3P MFO SX AS	1/2"	191	133
5″	Medium Plus 3P AFO SX AS	3/4"	191	133
5″	Medium Plus 3P BFO SX AS	1"	197	145
7"	Junior Plus 3P MFO SX AS	1/2"	241	133
7″	Junior Plus 3P AFO SX AS	3/4"	241	133
7"	Junior Plus 3P BFO SX AS	1"	247	145
10"	Senior Plus 3P MFO SX AS	1/2"	315	133
10"	Senior Plus 3P AFO SX AS	3/4"	315	133
10"	Senior Plus 3P BFO SX AS	1″	321	145
20"	Master Plus 3P MFO SX AS	1/2"	571	133
20"	Master Plus 3P AFO SX AS	3/4"	571	133
20"	Master Plus 3P BFO SX AS	1″	577	145



## **VARIANTS** available on minimum quantity

**FP** female plastic IN/OUT threads, BSP type 1/4", 3/8", 1/2", 3/4", 1".

**FP-NPT** female plastic IN/OUT threads, NPT type 3/4", 1".

**MP** male plastic IN/OUT threads, BSP type.

**AB** housings with opaque bowl, impermeable to the light.



### accessories



4

wall bracket wall bracket screws



3/4" and 1"brass



5", 7", 10" diffuser tubes